



DATA SHEET

Fast. Scalable. Efficient.

# NyTRO AP 2U24



Seagate<sup>®</sup> NyTRO<sup>®</sup> AP 2U24 is the cost-effective, scalable 2U storage rack for high-bandwidth, low-latency tasks, featuring dual 12Gb/s SAS controllers.



## Best-Fit Applications

- Small and mid-sized deployments
- High-bandwidth, low-latency environments
- 4K and 8K workflows, medical offices, surveillance
- Image sequence processing
- Hybrid tiered systems

## Key Advantages

Harness fast data transfers with a 12Gb/s SAS interface paired with Seagate NyTRO SSD drives.

Gain more space and performance while lowering TCO with a 2U rack storing up to 24 drives.

Build an efficient compute and storage environment with a fast SSD in a compact form factor.

Select controller performance and high-availability options to suit budget and/or software requirements with dual x86 controllers.

Support virtually any current or future network infrastructure with 10GbE, 25GbE, and 100GbE I/O options.

Dual 12Gb/s SAS controllers are compliant with the latest architecture standards for maximum data throughput.

Tap into increased reliability and business/operations continuity with fully redundant, hot-swappable components.

Right-size your configuration by purchasing only what you need.

Shares design and multiple FRUs with various Exos<sup>®</sup> products for modular, easy-to-service AP and EBOD ecosystems.

Expand your storage as your business grows with up to 8 chassis.



Specifications	
<b>Controller Specifications</b>	
Controller and Quantity	One or two AP-BV-1 Controllers, redundancy optional
CPU Type and Quantity Per Controller	AMD SP3 7292P EPYC CPU (8,12,16 Core)
Memory Type and Quantity Per Controller	4 x DDR4 - 3200MHz DIMM slots - 8, 16,32,64GB DIMM support +
Internal Boot Drive Per Controller	Dual NVMe M.2 Board with Single or Dual M.2 NVMe SSD
Onboard I/O	On-board Mellanox CX4 Dual Port 10/25GbE I/O 2 x 1GbE onboard connections (Management / Data)
PCIe Expansion	One low-profile, half-length PCI Express Gen 4 x16 Host Interface Slot, and one OCP v2.0 Gen 4x8 host interface slot
Storage Infrastructure	On each controller: Gen 4 x8 PCIe Lanes to 12G Broadcom SAS Controller, 12G x4 Mini-SAS HD External Expansion Ports
Inter-Controller Link	PCI Express Gen 3 x16 NTB Inter-controller Interface
<b>Chassis Specifications</b>	
Redundant Path	Yes (SAS only)
Management/Status Reporting	Redfish API + IPMI & SES
Device Support	12Gb/s SAS and 6Gb/s SATA SSDs
Max Drives Per Enclosure	up to 24 x 2.5-in SFF drives (for a full list of supported drives, please contact your account or sales manager)
Hot-Swappable Components	SSDs (in chassis data slots), power supply and cooling modules units (PCU), controllers
Physical	Height: 87.9mm / 3.46 in   Width: 443mm / 17.44 in   Depth: 630mm / 24.8 in   Width (w/ear mounts): 483mm / 19.01 in   Weight: 17kg / 38 lb   Weight (with drives): 30kg / 66 lb
<b>Power Requirements—AC Input</b>	
Input Power Requirements	100V-240V AC 60Hz/50Hz
Max Power Output per PSU	764W
<b>Environmental/Temperature Ranges</b>	
Operating/Nonoperating Temperature	ASHRAE A2, 5°C to 35°C (41°F to 95°F), derate 1°C/300m above 900m, 20°C/hr max rate of change / -40°C to 70°C (-40°F to 158°F)
Operating/Nonoperating Humidity	-12°C DP minimum, 8% RH to 85% RH, max DP 21°C / 5% to 100% noncondensing
Operating/Nonoperating Shock	5 Gs, 10ms, half sine pulses / 15 Gs, 10ms, half sine pulses
Operating/Nonoperating Vibration	0.21 Gs rms, 5Hz to 500Hz random / 1.04 Gs rms, 2Hz to 200Hz random
<b>Standards/Approvals</b>	
Safety Certifications	UL62368-1 ED3 (United States)   CAN/CSA-C22.2 No.60950-1-07/No.62368-1-14, 2nd Ed (Canada)   EN62368-1 (European Union)   IEC 62368-1 Ed3 (International)   CQC (China PRC – CQC Power Supplies)   BIS (India – BIS Power Supplies)
Ecodesign	Commission Regulation (EU) 2019/424 (Directive 2009/125/EC)
Emissions (EMC)	FCC CFR 47 Part 15 Subpart B Class A (United States)   ICES/NMB-003 Class A (Canada)   EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 (Europe)   AS/NZS CISPR 32 Class A (Australia/New Zealand)   VCCI Class A (Japan)   KS 32 Class A/KS 35 (S. Korea)   CNS 13438 Class A (Taiwan)
Harmonics	EN 61000-3-2 (EU)
Flicker	EN 61000-3-3 (EU)
Immunity	EN 55024 (EU)   KS 24/KS 35 (S. Korea)   CISPR 24/CISPR35
Environmental Standards	The RoHS Directive (2011/65/EU)   The WEEE Directive (2012/19/EU)   The REACH Directive (EC/1907/2006)   The Batteries Directive (2006/66/EC)
Standard Marks/Approvals	The RoHS Directive (2015/65/EU)   The WEEE Directive (2012/19/EU)   The REACH Directive (EC/1907/2006)   The Batteries Directive (2006/66/EC)

seagate.com



© 2020 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Exos, Nytro, and the Nytro logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. Intel and Xeon are trademarks of Intel Corporation or its subsidiaries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2051.3-2112US December 2021